



LIPTAI

MDG006R040SL

## MOSFETs Silicon 40V N-Channel MOS

### ■ Applications


- Load Switch
- Power management in portable/desktop PCs
- DC/DC Converters

### ■ Features

- High Current Capability
- Reliable and Rugged
- Low On-Resistance
- Capable of 4.5 V Gate Drive
- RoHS and Halogen-Free Compliant
- 100% UIS and RG Tested

### ■ Product Summary

$V_{DS}$	40	V
$I_D$	65	A
$R_{DS(ON)} , Typ @ 10V$	5.1	$m\Omega$
$R_{DS(ON)} , Typ @ 4.5V$	6.8	$m\Omega$
$Q_g$	15	nC



DFN5x6

Marking	Package	Packaging	Min. package quantity
MDG006R040SL	DFN5x6	Tape & Reel	5000





LIPTAI

MDG006R040SL

## ■ Absolute Maximum Ratings (T<sub>c</sub>=25°C unless otherwise noted)

Parameter	Symbol	Ratings	Unit
Drain-Source Voltage	V <sub>DS</sub>	40	V
Gate-Source Voltage	V <sub>GS</sub>	±20	V
Continuous Drain Current T <sub>c</sub> =25°C (Note 1)	I <sub>D</sub>	65	A
Continuous Drain Current T <sub>c</sub> =100°C (Note 1)		45	A
Drain Current-Pulsed (Note 1)	I <sub>DM</sub>	170	A
Total Dissipation	P <sub>D</sub>	50	W
Junction Temperature	T <sub>j</sub>	150	°C
Storage Temperature	T <sub>stg</sub>	-55-150	°C
Single Pulse Avalanche Energy (Note 2)	E <sub>AS</sub>	60	mJ

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.

## ■ Thermal Characteristics

Parameter	Symbol	Max	Unit
Maximum Junction-to-Case	R <sub>θJC</sub>	2.5	°C/W
Maximum Junction-to-Ambient (Note 3)	R <sub>θJA</sub>	50	°C/W

Note 1: Ensure that the channel temperature does not exceed 150°C.

Note 2: V<sub>DD</sub>=50V, T<sub>ch</sub>= 25°C(initial), L=0.5mH, R<sub>g</sub>=25Ω.

Note 3: The value of R<sub>θJA</sub> is measured with the device mounted on 1in2 FR-4 board with 2oz. Copper, in a still air environment with T<sub>A</sub>=25° C. The value in any given application depends on the user's specific board design.

Note: This transistor is sensitive to electrostatic discharge and should be handled with care.





LIPTAI

MDG006R040SL

## ■ Electrical Characteristics (T<sub>c</sub>=25°C unless otherwise noted)

Parameter	Symbol	Test Condition	Min	Typ	Max	Unit
<b>Static Parameters</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	V <sub>GS</sub> =0V, I <sub>D</sub> =250μA	40	-	-	V
Drain-Source Leakage Current	I <sub>DSS</sub>	V <sub>DS</sub> =40V, V <sub>GS</sub> =0V	-	-	1	μA
Gate-Body Leakage Current	I <sub>GSS</sub>	V <sub>GS</sub> =±20V, V <sub>DS</sub> =0V	-	-	±100	nA
Gate Threshold Voltage	V <sub>GS(TH)</sub>	V <sub>GS</sub> =V <sub>DS</sub> , I <sub>D</sub> =250μA	1.0	1.5	2.0	V
Drain-Source On Resistance	R <sub>DS(ON)</sub>	V <sub>GS</sub> =4.5V, I <sub>D</sub> =15A	-	6.8	8.5	mΩ
			T <sub>j</sub> =125°C	-	9.5	
		V <sub>GS</sub> =10V, I <sub>D</sub> =20A	-	5.1	6	
			T <sub>j</sub> =125°C	-	7.5	
<b>Dynamic Characteristics</b>						
Input Capacitance	C <sub>iss</sub>	V <sub>DS</sub> =20V, V <sub>GS</sub> =0V, f=1.0MHz	-	720	-	pF
Output Capacitance	C <sub>oss</sub>		-	230	-	pF
Reverse Transfer Capacitance	C <sub>rss</sub>		-	15	-	pF
Gate Resistance	R <sub>g</sub>	V <sub>DS</sub> =0V, V <sub>GS</sub> =0V, f=1.0MHz	-	1.1	-	Ω
<b>Switching Paramters</b>						
Turn-On Delay Time	t <sub>d(on)</sub>	V <sub>DS</sub> =20V, I <sub>D</sub> =20A, V <sub>GS</sub> =10V, R <sub>G</sub> =3Ω	-	3.5	-	ns
Turn-On Rise Time	t <sub>r</sub>		-	30	-	ns
Turn-Off Delay Time	t <sub>d(off)</sub>		-	12	-	ns
Turn-Off Rise Time	t <sub>f</sub>		-	8	-	ns
Total Gate Charge	Q <sub>g</sub>	V <sub>DS</sub> =20V, I <sub>D</sub> =20A, V <sub>GS</sub> =10V	-	15	-	nC
	Q <sub>g</sub> (4.5V)		-	7	-	nC
Gate-Source Charge	Q <sub>gs</sub>		-	3	-	nC
Gate-Drain Charge	Q <sub>gd</sub>		-	3	-	nC
<b>Source-Drain Characteristics</b>						
Diode Forward Voltage	V <sub>sd</sub>	V <sub>GS</sub> =0V, I <sub>S</sub> =10A	-	0.75	1.2	V
Reverse Recovery Time	t <sub>rr</sub>	V <sub>GS</sub> =0V, I <sub>F</sub> =20A, di/dt=100A/us	-	15.5	-	ns
Reverse Recovery Charge	Q <sub>rr</sub>		-	2.5	-	nC







LIPTAI

MDG006R040SL


## ■ Characteristics Curves




Output Characteristics





Transfer Characteristics



On Resistance Vs Drain Current



On Resistance Vs Gate Source Voltage

R<sub>dson</sub>-JunctionTemperature


Capacitance






LIPTAI


MDG006R040SL



Gate Charge Waveform



Source-Drain Diode Forward Voltage



Maximum Safe Operating Area



Note : The above characteristics curves are presented for reference only and not guaranteed by production test, unless otherwise noted.







## ■ Test Circuit & Waveform



Gate Charge Test Circuit & Waveform



Resistive Switching Test Circuit & Waveform



Unclamped Inductive Switching (UIS) Test Circuit & Waveform





LIPTAI

MDG006R040SL

## ■ DFN5x6 Package Dimensions

Unit: mm

Symbol	Min	Nom	Max	Symbol	Min	Nom	Max
A	0.90		1.10	k	1.15		1.35
A3	0.15		0.30	b	0.20		0.40
D	5.05		5.25	e	1.15		1.35
D1	4		4.2	L	0.50		0.65
D2	4.75		5.05	L1	0.43		0.55
E	5.85		6.15	H	0.55		0.68
E1	3.35		3.55	$\theta$	8°		12°
E2	5.55		5.85				

